## STORMWATER MAINTENANCE SCHEDULE DRYWELL

## MODIFIED TO CORRESPOND TO CARROLL COUNTY DETAILS

MONTHLY INSPECTION		
Inspection Item	Inspection Requirements	Remedial Action
Vegetative Cover and Erosion	Check overflow area for channelizing and bare spots.	Re-seed or re-plant in accordance with approved landscaping plans.  Re-grade if concentrated flow is causing rills or gullying over the facility.
SEASONAL INSPECTION AND AFTER A MAJOR STORM		
Inspection Item	Inspection Requirements	Remedial Action
Leaves and Debris	Check that gutters, downspouts and screens are clear of leaves and debris.	Clean out gutters, downspouts and screens and dispose of leaves and debris in an acceptable manner.
Inflow and Overflow	Check for misalignments, broken pipes, and blockages. Inlet pipe and surcharge overflow "Y or T" must be in good condition.	Repair any broken or faulty piping. Clear out any blockages.
Dewatering	Check observation wells for water level. Water stored in stone must dewater within 48 hours of rainfall. Noticeable odors or the presence of algae or stained water are indicators of anaerobic conditions and inadequate dewatering of the facility.	Excavate, remove, clean, and replace stone and sand in accordance with approved plans.
ANNUAL INSPECTION		
Inspection Item	Inspection Requirements	Remedial Action
Maintenance Access	Check for accessibility to facility.	Prevent excessive vegetative growth, erosion, and obstructions on access way.
Overall Function of Facility	Check that flow conveyance is operating as designed	Repair to good condition according to specifications on the approved plans.

Modifications
Martin B. Covington, III, P.E.
Carroll County Stormwater Management Program Engineer
April 9, 2020