



**NOTES:**

1. APRON SHALL BE CONSTRUCTED A MINIMUM OF 18 FEET FROM THE EDGE OF ROAD.
2. PAVEMENT SECTION TO BE 7 INCHES THICK NON-REINFORCED CONCRETE MDOT SHA MIX NO. 9 OR 1.5 INCHES HOT MIX SUPERPAVE 9.5 MM FOR SURFACE (PG 64S-22, LEVEL 1), 3.0 INCHES HOT MIX SUPERPAVE 19.0 MM FOR BASE (PG 64S-22, LEVEL 1), AND 6.0 INCHES GRADED AGGREGATE BASE (GAB).
3. COUNTY APPROVAL REQUIRED FOR ANY DESIGN MODIFICATIONS TO THIS DETAIL.
4. SWALE APRONS MAY BE USED ONLY WHERE UPGRADE DRAINAGE AREA IS 1-3 ACRES OR DISTANCE TO THE CREST OF HILL IS LESS THAN 150 FEET.

CARROLL COUNTY, MARYLAND DEPARTMENT OF PLANNING AND LAND MANAGEMENT	USE IN COMMON DRIVEWAY APRON WITH SWALE	PLATE NO.
		UIC 7

ISSUED:	REVISED:
REVISED:	REVISED: